



## Mobil Super 1000

Mobil Passenger Vehicle Lube , Australia

Premium Multigrade Passenger Vehicle Engine Oils

### Product Description

The Mobil Super 1000 products are a range of quality premium mineral motor oils designed to provide a high level of performance and protection under most operating conditions.

### Features and Benefits

Mobil Super 1000 is meticulously engineered for today's tougher engine specifications. It provides very good engine protection and extends engine life.

- Excellent wear protection
- Excellent engine cleanliness

### Applications

Mobil Super 1000 5W-30 is suitable for use in gasoline powered vehicles. Mobil Super 1000 10W-30, 10W-40, 15W-50 and 20W-50 are suitable for use in both gasoline and diesel powered vehicles. All Mobil Super 1000 products are ideally suited for less stressful driving conditions such as highway driving and lower consistent speed conditions.

### Specifications and Approvals

This product is recommended for use in applications requiring:	5W-30	10W-30
API CF		X
API Energy Conserving (SM)		X
ILSAC GF-4		X

This product meets or exceeds the requirements of:	5W-30	10W-30
API SJ		X
API SL	X	X
API SM	X	X
API SN	X	X
API SN Resource Conserving		X

### Properties and Specifications

Property	5W-30	10W-30
Grade	SAE 5W-30	SAE 10W-30

Property	5W-30	10W-30
Ash, Sulfated, mass%, ASTM D874	0.8	0.8
Density @ 15 C, g/ml, ASTM D4052	0.86	
Flash Point, Cleveland Open Cup, °C, ASTM D92	230	220
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683		3.2
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	11.1	10.5
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	68	65.5
Pour Point, °C, ASTM D97	-39	-36
Viscosity Index, ASTM D2270	155	149

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2019

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay

Southbank Vic 3006

+61 3 8633 8444


<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved